



fig. 1

General Description

Junckers SYLVApolish is a cleaning and maintenance polish for lacquered wooden floors that provides a water-repellent film.

Technical Data

Product:	Nonionic tenside, preservation agent	
pH Value:	Diluted:	Approx 8.0
	Undiluted:	Approx 8.0
Package size:	1 litre.	
Coverage:	Approx. 80-100 m ² per litre solution	
Application tool:	Well wrung out cloth or damp mop	
Substrate temperature:	Minimum 5°C.	
Dilution:	For weekly cleaning use 100 ml. to 10 litres of water. On high traffic floors the polish is used undiluted.	
Drying time:	Approx. 20-30 min.	
Cleaning of tools:	Water.	
Storage:	Lasts for several years if unopened and stored at 20°C.	

Directions for Use

New Floors

A thin layer of diluted SYLVApolish is applied using a soft lint-free cloth. For high traffic areas a coat of undiluted SYLVApolish is recommended.

Weekly Maintenance

To 10 litres of water add 100 ml of SYLVApolish. The polish is applied using a well wrung out cloth. For high traffic areas the floor can be treated more frequently. The amount of polish can be increased, if necessary.

Basic Cleaning

If the SYLVApolish does not make the floor sufficiently clean, Junckers SYLVAstrip basic cleaner can be used. Afterwards treat the floor as described under "New Floors".

Re-lacquering

Floors that have been treated with wax or polish will require sanding before re-lacquering.

Important!

Floors treated with SYLVApolish should not be buffed as this will make them slippery.

Important!

Always use a very well wrung cloth to prevent water damage.

Important!

For high traffic areas the floors can be treated more frequently. The amount of SYLVApolish can also be increased, if necessary.

Important!

Before use of the product, read the label on the container carefully.